



AC-HDVP-70T-M 70m HDBaseT Wallplate Extender

AdvanceConnex AC-HDVP-70T-M HDBaseT Wallplate extender feature with multiple input video port 1 x DisplayPort, 1 x HDMI and 1 x VGA+3.5mm audio, 2 x Programming (RS232) ports, bi-directional IR over single HDBaseT (RJ45) output.

User can simply select the input sources by pressing “SEL” button on the panel as well as selecting the different working modes with options manual, auto or Priority. The P1/P2 button function to control the equipment with RS232 control commands.

AC-HDVP-70T-M video resolution support up to 4k@30hz with the POC(power over cable) function.

Features:

- Resolution supported max 4K@30fps
- Support HDCP1.4
- Distance HD1080p 70m, 4K 35m
- Support bi-directional IR
- POC (power over Cable) function
- Auto switching, manual, priority working mode supported
- Build in button for switching/select the input source
- LED light indicator for video source

Specification:

Input	1 x DisplayPort, 1x HDMI, 1 x VGA+3.5mm audio, 2 x IR, 2 x Programming
Output	1 x HDBaseT (RJ45)
Control	Push button, RS232
Transmission distance	70m at 1080P via cat6 35m at 4K30 via cat6
Bandwidth	10.2Gbps
Power Supply	DC 12V 1.25A
Dimension (WxHxD)	Wallplate - 88x88x33mm Receiver - 115x84x16mm
Weight	Wallplate - 195g Receiver - 125g
Operating Temperature	-10°C to 40°C
Storage Temperature	-25°C to 55°C

Connection Diagram:

