

VGA KVM Switch

AS-21UA/41UA

Introduction:

AS-21UA/41UA 2/4ports KVM SWITCH, can control 2/4 servers via a single console (USB) and allows users to switch between computers via buttons on the front panel of the switch or hot key configuration on the keyboard. It is the simplest and most convenient solution for multi-computers management. Stable capability, durable and small design are the most important features for this series products.



Specification:

TYPE		AS-41UA	AS-21UA
Computer connections	Connect directly	4	2
Port selection		Front panel switches/ hot key	
LED' s	selected	4	2
	online	4	2
	power	1	1
Console ports	monitor	1*HD15 female	1*HD15 female
	keyboard	1*USB female	1*USB female
	mouse	1*USB female	1*USB female
	audio	1* audio output	1* audio output
PC ports		4*HD15 female	2*HD15 female
		4* audio input	2* audio input
Simulation		USB	USB
Power		AC220V/5W	AC220V/5W
Video resolution		2048*1536(max) ; DDC2B	2048*1536(max) ; DDC2B
Scan interval		5S	5S
Operating temp.		-10°C~50°C	
Storage temp.		-20°C~60°C	
Housing		Metal	
Weight		0.82kg	0.57kg
Dimension		132 x 92 x 43 mm	86 x 86 x 26.5 mm