

# Single-Rail LCD KVM Console VGA Series 17"



- \*Front LCD Console (keyboard, mouse, monitor 17" ) + KVM Module design (1/4/8/16ports); It's very flexible and convenient for combination;
- \*IP optional ( IP card could be installed inside KVM module);
- \*Extra prepositive USB mouse interface;
- \*Single port length: 462.6mm; Multi-ports length: 611mm

## 17" LCD Console Specification

Type		17" LCD Console – AS7100ULS(F)
LCD Monitor	Ratio	17" Screen, 4:3
	Video	SXGATFT-LCD
	Visible Square	337.920(H) × 270.336(V)
	Resolution	1280*1024 @60HZ(Optimum)/1920 * 1200 @60HZ(Max)
	Support Color	16.7M (RGB 6 bit + Hi_FRC)
	Contrast	1000 : 1 (Typ)
	Backlight	LED
	Pixel Pitch	0.264x0.297mm
	LEDMTBF	100,000 hours
	Input Power	12V
Keyboard	Keyboard	100Keys, detachable (9 different languages for choose)
	Compatible IBM/AT	Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
	Port	Standard PS/2; USB
	Using life	>1,000,000 Times
Mouse	Type	Touch Screen
	Port	Standard PS/2
	X/Y Resolution	>1000dots/inch, (40x40/mm)
	Using life	>1,000,000 Times
Installation Dimension	407.1*445*45mm	
Weight	6.15kg	



## KVM Module Specification

Type		1 Port(ULSV01)	4 Port(ULSV04)	8 Port(ULSV08)	16Port(ULSV16)
Model No. (Completed device)		AS7100ULS(F) + ULSV01 (AS-7100ULS)	AS7100ULS(F) + ULSV04 (AS-7104ULS)	AS7100ULS(F) + ULSV08 (AS-7108ULS)	AS7100ULS(F) + ULSV16 (AS-7116ULS)
Computer Connection	Direct Connects	1	4	8	16
	Maximum Connects	1	64	128	256
CPU Port Selection		/	OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional)		
Connectors	Console Connector	DB 37PIN			
	PC Connector	1 x VGA DB15, USB/PS.2	4 x VGA DB15, Female Blue	8 x VGA DB15, Female Blue	16 x VGA DB15, Female Blue
	Power	1 x DC Jack			
	Network Port	/	1xRJ45(Optional)		
	Key Switch	Connection Port Selection	/	KVM Operation Panel Digital keys	
Key Switch	KVM Reset	KVM Operation Panel Function Keys			
	IP Module Reset	/	1 x semi-embedded key		
	IP Module Default	/	1 x semi-embedded key		
LED's	Selected	/	Nixie Tube Display		
	Online	/	4 x Red	8 x Red	16 x Red
	IP Network	/	1 x Green, 1 x Orange		
Analog Mode	Keyboard/Mouse	USB, PS/2			
Resolution (Max)		1920 x 1200 @ 60HZ Local & Remote			
Scan time interval		3, 5, 10, 15, 20, 30, 40, 60s (3s by default)			
Operating Environment	Operating temperature	-10-50°C			
	Storage temperature	-20-60°C			
	Humidity	0-80%RH, No Condensation			
Physical Properties	Housing	Plastic	Metal		
	Dimension	50*77*24.5mm	148.4*445*45mm		
	Weight	0.18kg	2.7kg	3.32kg	4.96kg