



D2V17C0

DisplayPort to VGA Dongle



Introduction

SUNIX D2V17C0 DisplayPort to VGA dongle lets you connect a VGA computer monitor/project to a DisplayPort graphics card or other DisplayPort source, eliminating the expense of upgrading the monitor for compatibility. It supports PC resolutions of up to 1920x1200 and HDTV resolutions up to 1080p. This high-resolution dongle offers plug and play functionality to provide an active digital to analog conversion without software or drivers.

Features

- Converts a graphics card's DisplayPort output to a VGA output for use with a VGA monitor.
- Integrated chip to provide an active digital to analog conversion.
- Compliant with DisplayPort specification Ver1.2/1.1 (2.7 &1.62Gb/s).
- VGA output is compliant with VESA VSIS version 1, Rev.2 specification.
- Latching DP connector for a secure connection.
- Easy plug and play allows seamless display of your laptop and tablet content to your display.
- Certified by CE, FCC, VCCI, BSMI, C-Tick, and RoHS.

Specifications

Model	D2V17C0	
Description	DisplayPort to VGA Dongle	
Input Interface	Compliant with DisplayPort 1.2/1.1	
	Standard DisplayPort Male	
Output Interface	VGA RGB	
	VGA D-Sub 15-pin Female	



Display Resolution	VGA	640x480	
	SVGA	800x600	
	XGA	1024x768	
	720p	1280x720	
	WXGA+	1280x768	
	WXGA	1280x800	
	SXGA	1280x1024	
	WXGA+	1366x768	
	SXGA+	1400x1050	
	UXGA	1600x1200	
	WSXGA+	1680x1050	
	1080p	1920x1080	
	WUXGA	1920x1200	
Audio	Not Support		
Housing	ABS		
Power	DisplayPort Bus power 250mW @ 3.3VDC		
Environment	Operation temp. 0 °C ~ 40 °C (32-104°F)		
	Operation humidity: < 85% non-condensing		
	Storage temp10 °C ~ 85 °C (14~176°F)		
Dimension	57.8L x 22W x 13.2H mm		
Weight	15g (0.5oz)		
Regulatory Approvals	EUR: CE, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3		
	US: FCC Part 15 Class B		
	TAIWAN: BSMI: CNS13438		
	AS/NZS: C-Tick: CISPR22		
	JAPAN: VCCI		



Mechanical Drawings (Unit = mm)









