



Rack-Mountable KVM Switch Cat5 Series

Introduction:

The KS-3104/KS-3108/KS-3116 4ports/8 ports/16 ports PS/2 / USB CAT5 KVM (Keyboard, Video, Mouse) Switches are control units that allow access and control of up to 4(KS-3104) or 8 (KS-3108) or 16 (KS-3116) computers from a single PS/2 / USB keyboard, PS/2 / USB mouse, and monitor console.



Specification:

Type		4 Port	8 Port	16 Port	
Model		KS-3104	KS-3108	KS-3116	
Computer Connection	Direct Connects	4	8	16	
	Maximum Connects	64	128	256	
CPU Port Selection		OSD Menu, Front panel buttons, Hot Key, IP Remote Control (Optional)			
Connectors	Console Connector	Monitor	17" LED		
		Keyboard	1 x USB Type A Female		
		Mouse	1 x USB Type A Female		
		Expansion Interface	1 x USB Type A Female (Front expansion Keyboard, Mouse Interface)		
	PC Connector	Monitor, Keyboard/Mouse Switch Module	4 x VGA DB15 Female Blue, 4 x USB OR 4 x PS/2	8 x VGA DB15 Female Blue, 8 x USB OR 8 x PS/2	16 x VGA DB15 Female Blue, 16 x USB OR 16 x PS/2
		Switch Module Port	4 x RJ45	8 x RJ45	16 x RJ45
	Power		1 x DC Jack		
Network Port		1 x RJ45			
Key Switch	Connection Port Selection		KVM Operation Panel Digital keys		
	KVM Reset		1 x semi-embedded keys		
	IP Module Reset		1 x semi-embedded key		
	IP Module Default		1 x semi-embedded key		
LED's	Selected	4 x Green	8 x Green	16 x Green	
	Online	4 x Red	8 x Red	16 x Red	
	IP Network	1 x Green, 1 x Orange			
Analog Mode	Keyboard/Mouse		USB, PS/2		
Resolution (Max)		1920 x 1200 @ 60HZ Local & Remote			
Scan time interval		3, 5, 10, 15, 20, 30, 40, 60s (3s by default)			
Operating Environment	Operating temperature		-10-50°C		
	Storage temperature		-20-60°C		
	Humidity		0-80%RH, No Condensation		
Physical Properties	Housing		Metal		
	Size		432 x 155 x 44 mm		
	Weight		1.82KG		